

**E I DUPONT DE NEMOURS & CO INC**

DUPONT POLYMERS, ENGINEERING POLYMERS ACETAL RESINS PO BOX 80713,  
CHESTNUT RUN PLAZA WILMINGTON DE 19880

Material Designation: **DE9100, DE9100A, 200PL, 100, 100D, 107, 500(f1), 500D, 500HP, 507(f1), 900, 900HP, 900D**

Product Description: Acetal 'Polyoxymethylene' (POM), designated "Delrin" furnished as pellets.

<b>Color</b>	<b>Min. Thick. (mm)</b>	<b>Flame Class</b>	<b>HWI</b>	<b>HAI</b>	<b>RTI Elec</b>	<b>RTI Imp</b>	<b>RTI Str</b>	<b>IEC GWIT</b>	<b>IEC GWFI</b>
ALL	0.75	HB	-	-	50	50	50	-	-
	1.5	HB	3	0	105	85	90	-	-
	3.0	HB	3	0	105	85	90	-	-
	6.0	HB	2	0	105	85	90	-	-
	<b>CTI: 0</b>		<b>HVTR: 0</b>		<b>D495: 4</b>		<b>IEC BP: -</b>		

(f1) Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.

NOTE Material designations may be prefixed by the letters "DEL"

Report Date: 08/30/1977

Underwriters Laboratories Inc®

324299210

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.