

**CHEVRON PHILLIPS CHEMICAL CO L P**

1301 MCKINNEY ST HOUSTON TX 77010

Material Designation: **R-4(f1)**

Product Description: Polyphenylene Sulfide (PPS), glass reinforced, designated "RYTON"  
furnished as pellets.

<b>Color</b>	<b>Min. Thick. (mm)</b>	<b>Flame Class</b>	<b>HWI</b>	<b>HAI</b>	<b>RTI Elec</b>	<b>RTI Imp</b>	<b>RTI Str</b>	<b>IEC GWIT</b>	<b>IEC GWFI</b>
BK	0.38	V-0	-	-	130	130	130	-	-
	0.71	V-0	4	1	200	200	200	-	-
	1.5	V-0	0	0	220	200	220	-	-
	1.8	5VA	-	-	220	200	220	-	-
	3.0	V-0, 5VA	0	0	220	200	220	-	-
	6.0	V-0, 5VA	0	0	220	200	220	-	-
<b>CTI: 4</b>			<b>HVTR: 4</b>		<b>D495: 5</b>		<b>IEC BP: -</b>		

(f1) Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.

Report Date: 12/07/1982

Underwriters Laboratories Inc®

984485002

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.