


Core **PQ32/30**



Effective parameters			
	Parameter	Value	Unit
$\Sigma(I/A)$	core factor (C1)	0.447	mm ⁻¹
Ve	effective volume	12500	mm ³
Le	effective length	74.7	mm
Ae	effective area	167	mm ²
Amin	minimum area	142	mm ²
m	PQ32/30	≈ 57	g/set

Dimensions for product: PQ32/30						
	Nom	Tol +	Tol -	Max	Min	Unit
A	33.00	0.50	0.50	33.50	32.50	mm
B	22.00	0.50	0.50	22.50	21.50	mm
C					19.00	mm
D2	27.50	0.50	0.50	28.00	27.00	mm
D3	13.50	0.25	0.25	13.75	13.25	mm
E					5.50	mm
F					11.60	mm
H1	30.30	0.25	0.25	30.55	30.05	mm
H2	21.30	0.30	0.30	21.60	21.00	mm

Inductance factor				
Material	Value	Tol +	Tol -	Unit
3C94	5600	25%	25%	nH/turns ²
3C95	6570	25%	25%	nH/turns ²
3C96	5040	25%	25%	nH/turns ²
3C97	6570	25%	25%	nH/turns ²
3F36	3200	25%	25%	nH/turns ²
3F46	2000	25%	25%	nH/turns ²

Power loss: 3C94				
Measuring conditions			Max	Unit
100 kHz	200 mT	100 °C	6.300	W/set
Power loss: 3C95				
Measuring conditions			Max	Unit

Core

PQ32/30

Power loss: 3C95				
Measuring conditions			Max	Unit
100 kHz	200 mT	100 °C	6.000	W/set
100 kHz	200 mT	25 °C	6.500	W/set
Power loss: 3C96				
Measuring conditions			Max	Unit
100 kHz	200 mT	100 °C	5.600	W/set
400 kHz	50 mT	100 °C	2.400	W/set
Power loss: 3C97				
Measuring conditions			Max	Unit
100 kHz	200 mT	60 °C	6.300	W/set
100 kHz	200 mT	120 °C	6.000	W/set
100 kHz	200 mT	140 °C	7.500	W/set
Power loss: 3F36				
Measuring conditions			Max	Unit
500 kHz	50 mT	100 °C	1.900	W/set
500 kHz	100 mT	100 °C	14.000	W/set
Power loss: 3F46				
Measuring conditions			Max	Unit
1000 kHz	50 mT	100 °C	8.600	W/set
3000 kHz	10 mT	100 °C	5.800	W/set

Bsat					
Measuring conditions			Material	Min	Unit
25 kHz	250 A/m	100 °C	3C94	320	mT
25 kHz	250 A/m	100 °C	3C95	330	mT
25 kHz	250 A/m	100 °C	3C96	340	mT
25 kHz	250 A/m	100 °C	3C97	330	mT
25 kHz	250 A/m	100 °C	3F36	340	mT
25 kHz	250 A/m	100 °C	3F46	330	mT

Accessories		
Ordering name	Description	Ordering code
CLM/P-PQ32/30	Clamp, with ground pin	F0MPQ03230CLMP000P
CPV-PQ32/30-1S-12PD-Z	Coil former, termoplastic, vertical	F0PPQ03230CV01112P
CPV-PQ32/30-1S-12P-Z	Coil former, termoplastic, vertical	F0PPQ03230CV00112P