



LACC




All dimensions in mm


Leaded Inductors





Typical Q vs Frequency(f)



Typical L vs Frequency(f)



Typical L vs Current



Part No	Inductance L (µH)	f _l (MHz)	Tol ± (%)	Q min	f _Q (MHz)	SRF min (MHz)	DCR max (Ω)	Rated DC Current (A)
LACC-1R0X-YY	1	1	10,20	60	25.2	175	0.09	2
LACC-1R2X-YY	1.2	1	10,20	60	7.96	157	0.1	1.95
LACC-1R5X-YY	1.5	1	10,20	60	7.96	144	0.11	1.9
LACC-1R8X-YY	1.8	1	10,20	60	7.96	135	0.12	1.85
LACC-2R2X-YY	2.2	1	10,20	60	7.96	121	0.15	1.7
LACC-2R7X-YY	2.7	1	10,20	60	7.96	113	0.15	1.65
LACC-3R3X-YY	3.3	1	10,20	60	7.96	103	0.23	1.1
LACC-3R9X-YY	3.9	1	10,20	60	7.96	96	0.3	1.05
LACC-4R7X-YY	4.7	1	10,20	60	7.96	89	0.33	1
LACC-5R6X-YY	5.6	1	10,20	60	7.96	85	0.37	0.9
LACC-6R8X-YY	6.8	1	10,20	50	7.96	72	0.45	0.875
LACC-8R2X-YY	8.2	1	10,20	50	7.96	66	0.63	0.84
LACC-100X-YY	10	1	10,20	50	7.96	57	0.73	0.8
LACC-120X-YY	12	0.02	10,20	50	2.52	51	1.35	0.65
LACC-150X-YY	15	0.02	10,20	60	2.52	47	1.5	0.61
LACC-180X-YY	18	0.02	10,20	60	2.52	44	1.65	0.565
LACC-220X-YY	22	0.02	10,20	60	2.52	41	1.86	0.51
LACC-270X-YY	27	0.02	10,20	60	2.52	38	2.1	0.49
LACC-330X-YY	33	0.02	10,20	60	2.52	36	2.4	0.45
LACC-390X-YY	39	0.02	10,20	55	2.52	33	2.7	0.43
LACC-470X-YY	47	0.02	10,20	55	2.52	31	3	0.39
LACC-560X-YY	56	0.02	10,20	55	2.52	29	3.4	0.36

Material : Ferrite

SPQ :

Packing Form	Loose / Box		Reel		Taped / Ammopack	
Axial	2000	[-00]	3000	[-01]	1000 [-02]	
Preformed	1500	[-20]				