

DESCRIPTION / BESCHREIBUNG	MMS-201					MMS-202					MMS-203					MMS-204				
	DIAMETER mm	3,8					3,8					3,8					6,0			
LENGTH mm	18					25,2					12,7					25,7				
FORM																				
SWITCH AVAILABLE	1	2	3	4	5	1	2	3	4	5	1	2	3	4	5	1	2	3	4	5
CONTACT FORM	A	A	A	B	C	A	A	A	B	C	A	A	A	B	C	A	A	A	B	C
CONTACT RATING WVA	10	-	-	-	-	10	-	-	-	-	1	-	-	-	-	10	10	-	5	5
CONTACT VOLTAGE VDC	100	-	-	-	-	100	-	-	-	-	24	-	-	-	-	200	200	-	175	175
VAC	100	-	-	-	-	100	-	-	-	-	24	-	-	-	-	140	265	-	125	125
SWITCHING CURRENT A	0,5	-	-	-	-	0,5	-	-	-	-	0,1	-	-	-	-	0,5	0,3	-	0,25	0,25
CARRY CURRENT A	0,5	-	-	-	-	0,5	-	-	-	-	0,3	-	-	-	-	1	1,4	-	1,5	1,5
BREAKDOWN VOLTAGE VDC	150	-	-	-	-	150	-	-	-	-	150	-	-	-	-	250	400	-	200	200
TOTAL RESISTANCE mΩ	100	-	-	-	-	100	-	-	-	-	100	-	-	-	-	100	100	-	100	100
HOUSING MATERIAL	PA66GF	-	-	-	-	PA66GF	-	-	-	-	PA66GF	-	-	-	-	PA66GF	PA66GF	-	PA66GF	PA66GF
HOUSING COLOR	●	-	-	-	-	●	-	-	-	-	●	-	-	-	-	●	●	-	●	●
CABLE TYPE	UL1061	-	-	-	-	UL1061	-	-	-	-	UL1569	-	-	-	-	UL1569	UL1569	-	UL1569	UL1061
CABLE AWG	26	-	-	-	-	26	-	-	-	-	20	-	-	-	-	24	24	-	24	24
CABLE COLOR	●	-	-	-	-	●	-	-	-	-	●	-	-	-	-	●	●	-	●	●●

DESCRIPTION / BESCHREIBUNG	MMS-205					MMS-210					MMS-214				
	DIAMETER mm	6,0					5,6					5			
LENGTH mm	40,1					25,2					16				
FORM															
SWITCH AVAILABLE	1	2	3	4	5	1	2	3	4	5	1	2	3	4	5
CONTACT FORM	A	A	A	B	C	A	A	A	B	C	A	A	A	B	C
CONTACT RATING WVA	10	10	50/70	5	5	10	10	-	5	-	10	-	-	3	3
CONTACT VOLTAGE VDC	200	200	300	175	175	200	200	-	175	-	100	-	-	50	50
VAC	140	265	350	125	125	140	265	-	125	-	100	-	-	50	50
SWITCHING CURRENT A	0,5	0,3	0,7	0,25	0,25	0,5	0,3	-	0,25	-	0,5	-	-	0,2	0,2
CARRY CURRENT A	1	1,4	2,5	1,5	1,5	1	1,4	-	1,5	-	0,5	-	-	0,5	0,5
BREAKDOWN VOLTAGE VDC	250	400	500	200	200	250	400	-	200	-	180	-	-	100	100
TOTAL RESISTANCE mΩ	100	100	100	100	100	100	100	-	100	-	150	-	-	150	150
HOUSING MATERIAL	PA66GF	PA66GF	PA66GF	PA66GF	PA66GF	PA66GF	PA66GF	-	PA66GF	PA66GF	PA66GF	-	-	PA66GF	PA66GF
HOUSING COLOR	●	●	●	●	●	●	●	-	-	-	●	-	-	●	●
CABLE TYPE	UL1569	UL1569	UL1569	UL1569	UL1561	UL1569	UL1569	-	UL1569	UL1061	UL1061	-	-	UL1061	UL1061
CABLE AWG	24	24	24	24	24	24	24	-	24		28	-	-	28	28
CABLE COLOR	●	●	●	●	●●●	●	●	-	●	●●●	●	-	-	●	●●●

MAGNETS / MAGNETE



DESCRIPTION / BESCHREIBUNG	MMA-201		MMA-202		MMA-203		MMA-204		MMA-205		MMA-210		MMA-214	
	SWITCH AVAILABLE	1	2	1	2	1	2	1	2	1	2	1	2	1
CONTACT FORM	NdFeB 	Ferrite 	NdFeB 	Ferrite 	NdFeB 	Ferrite 	NdFeB 	Ferrite 	NdFeB 	Ferrite 	NdFeB 	Ferrite 	NdFeB 	Ferrite 